38-083-12
GARRISON QUADRANGLE
193 KY.-7 OHIO
N3830-W8300/15
DIAGRAM NJ 17-4
HUNTINGTON

UNITED STATES DEPARTMENT OR THE INTERIOR GEOLOGICAL SURVEY


Carter, Greenup, and Lewis Counties, Kentucky; Scioto County, Ohio

Final adjustment of 1962

Edition of 11/24/76

PR: LFB/sws

OTWAY (16)



VANCEBURG (194 KY.-8 OHIO)

NGS (USC&GS) VERTICAL CONTROL DATA

A. Quadrangle 380831

INDEX OF PERMANENT MARKS

MARK (USGS)	PAGE NO.	MARK (USGS)	PAGE NO.
528	3	4 JWM 1947 676	8
529	3	6 JWM 1947 789	8
566		7 JWM 1947 625	8
659	3	8 JWM 1947 1094	9
692	3	9 JWM 1947 741	10,9
721	3	10 JWM 1947 672	9
RESET 1950 (OHIO 516)	3	13 JWM 1947 824	10
PTS NO 8 1910 522	3	14 JWM 1947 849	10
TT STA NO 44 M 1929	3,4,11	15 JWM 1947 1007	10
TT STA NO 45 M 1929	3,7	16 JWM 1947 753	10
TT STA NO 46 M 1929	4,8	19 JWM 1947 1123	11
TT STA NO 47 M 1929	4	20 JWM 1947 614	11
TT STA NO 53 M 1929	4,12	21 JWM 1947 725	11
TT STA NO 54 M 1929	4,11,12	22 JWM 1947 552	11
TT STA NO 55 M 1929	4	86 EOM 1949 622	12
TT STA NO 56 M 1929	4,9		
TT STA NO 59 M 1929	5,9	USED	
TT STA NO 60 M 1929	5		
TT 8 TWC 1947 743	9	573	7
TT 9 TWC 1947 912	9	BM 81	8
1 JWM 1947 662	6	BM 82	12
2 JWM 1947 935	6		
3 JWM 1947 895	6	NGS	
4 JWM 1947 740	6		
5 JWM 1947 613	6	D 79 1935	5
6 JWM 1947 524	5	E 79 1935	7
7 JWM 1947 554	5	G 79 1935	12
1 JWM 1947 601	7		
2 JWM 1947 784	7		
3 JWM 1947 758	7,10		

LINE 1 (Cont'd.)	Feet
Reference mark; 40 ft N. of tablet; at signal tower 5604; on W. corner of base; chiseled square	544.65
St. Paul; 4.6 ft from SE. corner and in line with E. edge of St. Paul Church; in lawn; in concrete post flush with ground; standard tablet stamped 'TT STA NO 46 M 1929"	553.127
Reference mark; at rd. crossing; at foot of double signal tower 5567; on SE. corner of telphone box; chiseled square	544.58
Firebrick; 49 ft from SW. corner and in line with W. edge of C. & O. Ry. station; 225 ft SW. of milepost 554; on edge of grassy embankment; in concrete post; standard tablet stamped 'TT STA NO 47 M 1929" (Reported not found, 1948)	546.360
LINE 2.	
By M. C. McClellan, 1929; Book B3521	
'TT STA NO 44 M 1929" (Described in line 1)	534.748
Upperbruce, 1.1 mi SW. of; 4.6 mi SW. of Garrison, along C. & O. Ry.; about 600 ft S. of Red Brush School; 30 ft E. of crossing of rd. to Red Brush School; 3 ft S. of N. end of Ry. right-of-way fence; in concrete post; standard tablet stamped "TT STA NO 55 M 1929"	552.663
Tannery, 1.0 mi NW. of; in line with N. side of Tannery School; 15 ft from NW. corner; 10 ft S. and 5 ft W. of well; in concrete post; standard tablet stamped "TT STA NO 54 M 1929"	562.310
Tannery, 4.0 mi S. of; 5.5 mi N. of State Highway 59 bridge over Kinniconick Creek, along Kinniconick Creek Road; 3.2 mi S. of Tannery School; 12 ft N. of SW. corner of Armstrong Church (built about 1953); 28 ft S. of NW. corner of church; 0.6 ft W. of W. wall of church; in concrete post; standard tablet	4
stamped 'TT STA NO 53 M 1929 652"	652. 984
LINE 3.	
By M. C. McClellan, 1929; Book B3521	
U. E., Garrison, 0.7 mi E. of; chiseled square (Described in line 1)	537.05
Garrison, 0.7 mi E. of, thence 3.3 mi SE.; 0.8 mi N. of Rexton Post Office; 35 ft S., thence 48 ft E. of forks of old state rd. E.; on top of bank; in concrete post; standard tablet stamped "TT STA NO 56 M 1929" (Reported destroyed, 1961)	643.122

GARR:	LSON	QUADRANGLE
Book	B352	21

193 KY.-7 OHIO

M. C. McClellan

38-083-12

1929

LINE 4.

Feet

By M. C. McClellan, 1929; Book B3521

Ruggles, 0.3 mi N. of, thence 3.4 mi NE. along Lambert Branch and Dummit Ridge rd.; 300 ft W. of dwelling of Arthur Dummit; 25 ft N. of rd.; 9 ft S. of large chestnut tree; in top of N. edge of sandstone outcrop; standard tablet stamped "TT STA NO 60 M 1929"

1144.449

LINE 5.

C. E. Walker, 1929; Book B3517

Upper Three Prong School; 4.7 mi NW. of Kehoe; 77 ft E. of SE. corner of school building; 3.5 ft S. of NW. corner fence post; in concrete post; standard tablet stamped "TT STA NO 59 M 1929"

747.570

LINE 6.

By J. W. McLaughlin, 1947; Book AV 36

"D 79 1935" (NGS)

596.875

U. E., Friendship, 0.1 mi W. of post office along U. S. Highway 52; at bridge over Turkey Creek; on top of the downstream end of the E. abutment, and near the junction of the SE. wingwall; USED chiseled square (This mark replaces bench mark 'C 79 1935" which was destroyed) (Tied by NGS, 1940)

535.633

Friendship, 1.0 mi SW. of, along U. S. Highway 52; 30 ft W. of center of junction of driveway W. to residence of H. M. Dobson; in SE. headwall of concrete culvert; standard tablet stamped "7 JWM 1947 554"

553.940

Reference mark; 120 ft N. of tablet; 25 ft W. of center of U. S. Highway 52; on E. headwall of concrete culvert; chiseled square

553.18

U. E., Friendship, 2.0 mi SW. of, along U. S. Highway 52; 30 ft N. of barn on SE. side of hwy.; 20 ft E. of center of junction of hwy. and rd. SE.; on SE. headwall of concrete culvert; chiseled square

546.49

Friendship, 3.0 mi SW. of, along U. S. Highway 52; at NE. entrance to Pond Run Methodist Epsicopal Church; in first step; standard tablet stamped "6 JWM 1947 524"

524.543

Reference mark; 300 ft SE. of tablet; 25 ft W. of centerline of junction of U. S. Highway 52 and Pond Run Road; on head of concrete culvert; chiseled square

523.78

LINE 6 (Cont'd.)	Feet
Reference makr, 0.4 mi SW. of tablet; at Shawnee C. C. c. camp; 45 ft N. of centerline of rd.; on E. concrete wall of grease pit; chiseled square	706.45
U. E., Pond Lick Church; 2.4 mi NW. of Friendship, along State Highway 125; at NE. entrance to church; on SE. concrete step; chiseled square	571.23
"E 79 1935" (NGS)	607.689
LINE 7.	
J. W. McLaughlin, 1947; Book AV 36	
Quincy, 0.2 mi from left bank of thio River; about 650 ft above C. & O. Ry. culvert over Briery Creek; about 500 ft below station; about 275 ft below rd. to landing; on property of C. & O. Ry.; 14 ft landside from centerline of landside track; 5 ft from fence; in concrete pedestal; on 2-in. iron pipe; USED standard	
Cap designated "573"	542.510
"TT STA NO 45 M 1929" (Described in line 1)	544.011
U. E., Quincy, 0.7 mi SE. of, along graded rd.; at SE. end of bridge; on S. wingwall; chiseled square	545.08
Quincy, 1.9 mi SE. of, along graded rd.; 20 ft SW. of centerline of T-rd. E.; at N. end of wooden bridge; in W. wingwall; standard tablet stamped "1 JWM 1947 601"	601.043
Reference mark; 65 ft E. of tablet; 15 ft S. of centerline of rd.; in base on N. side of 10-in. sycamore tree; rail spike	603.12
Quincy, 1.9 mi SE. of, along graded rd., thence 1.9 mi NE.; 60 ft NE. of barn on NW. side of rd.; 20 ft NW. of centerline of rd.; 10 ft NE. of fence corner; in concrete post; standard tablet stamped "2 JWM 1947 784" (Reported destroyed, 1967)	784.210
Reference mark; 90 ft E. of tablet; 20 ft SE. of centerline of rd.; in root on W. side of 10-in. sycamore tree; copper nail and washer	783.08°
Quincy, 1.9 mi SE. of, thence 3.9 mi NE.; 2.4 mi SW. of Letitia Post Office; 50 ft NW. of centerline of rd. fork; 15 ft W. of centerline of rd. N.; in concrete post; standard tablet stamped "3 JWM 1947 758"	757.756
Reference mark; 340 ft SW. of tablet; 15 ft SE. of centerline of rd.; in base on NW. side of 10-in. twin walnut trees; rail spike	753.68

Feet

574.68

553.127

LINE 7. (Cont'd.)

culvert; chiseled square

"TT STA NO 46 M 1929" (Described in line 1)

1947

LINE 8.	Feet
By J. W. McLaughlin, 1947; Book AV 36	
"TT STA NO 59 M 1929" (Described in line 5)	747.570
Rexton, 3.7 mi S. of post office, along Montgomery Mountain rd.; 21 ft SW. of twin sysamore trees; in concrete post; standard tablet stamped "TT 9 TWC 1947 912"	912.000
Reference mark; 180 ft NW. of tablet; 10 ft E. of centerline of rd.; in root on W. side of 6-in. oak tree; copper nail and washer	922.35
Rexton, 1.8 mi S. of, along Montgomery Mountain rd.; 19 ft W. of SW. corner of yard at dwelling of V. Lambert; 9 ft E. or centerline of rd.; in concrete post; standard tablet stamped "TT 8 TWC 1947 743" (Reported destroyed, 1961)	743.099
U. E., Rexton, 0.2 mi S. of; 50 ft SW. of centerline of forks at Y-rd. SW.; at W. end of bridge; on S. wingwall; chiseled square	665.56
"TT STA NO 56 M 1929" (Described in line 3)	643.122
York, 3.3 mi NW. of; about 200 ft N. of cemetery; 20 ft NE. of centerline of Y-rd. forks; in concrete post; standard tablet stamped "8 JWM 1947 1094"	1094.164
Reference mark; 40 ft SW. of tablet; 20 ft SW. of centerline of rd.; in root on NW. side of 8-in. maple tree; copper nail and washer	1093.17
York, 1.3 mi SW. of; 30 ft SW. of centerline of T-rd. W.; in concrete post; standard tablet stamped "9 JWM 1947 741"	741.261 ⁻
Reference mark; 60 ft N. of tablet; in root on SE. side of 36-in. oak tree; copper nail and washer	741.57
U. E., York; at post office; on NE. corner of first step; chiseled square	709.86
York, l.1 mi E. of; at SE. end of bridge; in E. wingwall; standard tablet stamped "10 JwM 1947 672"	672.017
Reference mark; 60 ft NW. of tablet on W. wingwall of bridge; chiseled square	671.92
U. E., York, 2.1 mi E. of; 150 ft E. of barn on S. side of rd.; 15 ft S. of centerline of rd.; on SE. headwall of concrete culvert; chiseled square	663.43

GARRISON QUADRANGLE Book AV 36	193 ку7 оніо	M. C. McClellan 1947	38-083-12 10
	LINE 9.		Feet
By J. W. McLaughlin, 1947; Boo	k AV 36		
"3 JWM 1947 758" (Described i	n line 7)		757.756
York, 3.9 mi N. of, along grad 10 ft E. of centerline of rd in concrete post; standard t	.; 4 ft N. of 16-in	. white oak tree;	823.735
Reference mark; 75 ft S. of ta in root on W. side of 10-in.			822.85.
York, 1.9 mi N. of, along grad W. side of rd.; 2 ft SE. of line of rd.; in concrete pos "14 JWM 1947 849"	SE. corner of shed;	10 ft W. of center-	849.565
Reference mark; 420 ft N. of t ft W. of centerline of rd.; rail spike	ablet; 15 ft SW. of in base on SE. side	small bridge; 10 of 16-in. oak tree;	865.12
U. E., York; chiseled square (Described in line 8)	709.86
	LINE 10.		
By J. W. McLaughlin, 1947; Boo	k AV 36		
"9 JwM 1947 741" (Described i	n line 8)		741.261
Brushart, 1.5 mi NE. of, along of centerline of junction of tablet stamped "15 JWM 1947	Y-rd. W.; in concre		1007.568
Reference mark; 30 ft SW. of t on top of rock ledge; chisel		centerline of rd.;	1004.54

U. E., Brushart, 0.6 mi NE. of, along Leatherwood Creek rd.; at

Brushart; in village of; 4 ft SW. of SW. corner of church; in concrete post; standard tablet stamped "16 JWM 1947 753"

Reference mark; 70' ft W. of tablet; 40 ft W. of centerline of rd.; in root on SE. side of 12-in. sycamore tree; copper nail

808.00

752.995

750.99

SW. end of bridge; on W. wingwall; chiseled square

and washer

LINE 12.

By J. W. McLaughlin, 1947;; Book AV 36

"TT STA NO 54 M 1929" (Described in line 2)

GARRISON QUADRANGLE

"19 JWM 1947 1123"

"20 JWM 1947 614"

washer

washer

Book AV 36

"TT STA NO 44 M 1929" (Described in line1) (Also in line 2)

534.748

562.310

LINE 12 (Cont'd.)

Feet

Garrison, 0.9 mi NE. of; on left bank of Ohio River; 200 ft from top of river bank; 55 ft SW. of 36-in. maple tree; 50 ft above road to landing; 49 ft SE. of spike in 20-in. elm tree, 45 ft SW. of downstream land corner of stone steps; 30 ft below house; in yard of John Warren; on 4-in. iron pipe mounted on an 18-in. by 18-in. concrete slab with a bolt in the center; USED standard cap designated "BM 82"

528.970

LINE 13.

By E. O. Miner, 1949; Book AV 100

"TT STA NO 53 M 1929 652" (Described in line 2)

652.984

U. E., Tannery, 1.0 mi NW. of, thence 2.0 mi S.; at E. end of cleared field; 20 ft S. of centerline of rd.; in base on W. side of 6-in. sycamore tree; spike nail

562.91

Armstrong School, 1.5 mi N. of; 6.5 mi SE. of Vanceburg; 1.0 mi NW. of Tannery, thence 1.0 mi S.; 47 ft NE. of, and 6 ft lower than old and new roadbeds forming Y-rd.; 1 ft NW. of boundary fence of Lewis County Wildlife Area; in concrete post; standard tablet stamped "86 EOM 1949 622"

622.358

U. E., Armstrong School, 2.5 mi N. of; across rd. from barn; 15 ft S. of middle of culvert; in base on E. side of 24-in. walnut tree; spike

572.66

U. E., Armstrong School, 2.9 mi N. of; 20 ft SE. of junction of T-rd.; at SW. corner of bridge; on top of stone abutment; chiseled square

572.28

"TT STA NO 54 M 1929" (Described in line 2) (Also in line 11)

562.310

LINE 14.

By E. V. Bon Durant, 1959; Book AV 758

"G 79 1935" (NGS)

767.121

HORIZONTAL CONTROL NORTH AMERICAN DATUM OF 1927

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

38-083-12
GARRISON QUADRANGLE
193 KY.-7 OHIO
N3830-W8300/15
DIAGRAM NJ 17-4
HUNTINGTON

Greenup and Lewis Counties, Kentucky; Scioto County, Ohio


Edition of 5/24/77

VANCEBURG

(194 KY .- 8 OHIO)

PR: CRV/rmm

Plane coordinates are based on Lambert projection, Kentucky, Morth Zone and Ohio, South Zone Only the permanent marks are listed for control classified obsolete and are not shown on sketch



DISCLAIMER

We no longer attest to the validity of the positions listed for horizontal control established by transit traverse procedures. This control is now considered OBSOLETE and is included in this list for the purpose of identification only.

INDEX OF PERMANENT MARKS

MARK (USGS)	PAGE NO.	LINE NO.
PTS NO 8 1910 OHIO 522	Ł.	
TT STA NO 44 M 1929	5 3 3 3 5 5 3 3	
TT STA NO 45 M 1929	3	
TT STA NO 46 M 1929	3	
TT STA NO 47 H 1929	3	
TT STA NO 53 M 1929 652	5	
TT STA NO 54 M 1929	3	
TT STA NO 55 M 1929	3	
TT STA NO 56 M 1929		
TT STA NO 59 M 1929	4	
TT STA NO 60 M 1929	4	
TT 1 TWC 1947	4	
TT 2 TWC 1947	4	•
TT 3 TWC 1947	5 5 5	
TT 8 TWC 1947 743	5	•
TT 9 TWC 1947 912	5	
86 EOM 1949 622	5	
USED		
573	4	
MGS .		
D 79 1935	4	
E 79 1935		
POND RUN STATE FOREST LOOKOUT TOWER 1953	5 6	1

STATION

DESCRIPTION PLANE COORDINATES, FEET

LATITUDE 0 1 11

LONGITUDE

The following positions are considered OBSOLETE. To be used only to locate permanent marks in the field.

By S. H. Moyers, 1929: Books C9006-7

Garrison; at Chesapeake and Chio Railway station; 19 ft E. of semaphore; in top of concrete stoop; standard tablet stamped "IT STA NO 44 M 1929"

Ky. N.)

X = 2.307.710

Y = 405.782

38 36 33.71

83 10 23.39

Quincy; 350 ft SW. of C. & O. Ry. station; 33 ft E. of rd. crossing of eastbound track; 8 ft E. of RR. signpost; in concrete post; standard tablet stamped "IT STA NO 45 M 1929"

X = 2.319.565 Y = 411.376

38 37 27.61

83 07 53.20

St. Paul; 5 ft from SE. corner of, and in line with E. edge of St. Paul Church; in concrete post flush with lawn; standard tablet stamped "TT STA NO 46 M 1929"

X = 2,331,032 Y = 427,943

38. 40 09.96

83 05 26.09

Firebrick; 49 ft from SW. corner of, and in line with W. edge of C. & O. Ry. station; 225 ft SW. of milepost No. 554; on edge of grassy embankment; in concrete post; standard tablet stamped "TT STA NO 47 M 1929" (Not found, 1948)

X = 2.341.892

Y = 435,777

38 41 26-02

83 03 07.89

By S. H. Moyers, 1929; Books C9006-7

Tannery, 1.0 mi W. of; in line with N. face of, and 15 ft from NW. corner of Tannery School; 10 ft S. and 5 ft W. of well: in concrete post; standard tablet stamped "TT STA NO 54 M 1929"

X = 2.290.237

Y = 384.583

38 33 06.12

83 14 06.45

Upperbruce, 1.1 mi SW. of; 4.6 mi SW. of Garrison, along RR.; 600 ft S. of Red Brushy School; 30 ft E. of rd. crossing to school; 3 ft S. of M. end of right-of-way fence; in concrete post; standard tablet stamped "TT STA NO 55 M 1929"

X = 2.299.889

Y = 391.629

38 34 14.70

83 12 03.94

Garrison, 0.7 mi E. of, thence 3.3 mi SE.; 0.8 mi N. of Rexton Post Office; 35 ft S. and 48 ft E. of fork of old state rd. E.; on top of bank; in concrete post; standard tablet stamped "TT STA NO 56 M 1929" (Reported destroyed, 1961)

X = 2,322,752

Y = 395.258

38 34 47.90

83 07 15.53

STATION DESCRIPTION
PLANE COORDINATES. FEET

LATITUDE

LONGITUDE

OBSOLETE MARKS (Cont'd.)

By S. H. Moyers, 1929; Books C9006-7

Kehoe, 4.7 mi NW. of; 77 ft E. of SE. corner of Upper Three Prong School; 3.5 ft S. of NW. corner fencepost; in concrete post; standard tablet stamped "TT STA NO 59 M 1929"

X = 2.324.844

Y = 367,586

38 30 14.12

83 06 53.48

Ruggles, 0.3 mi N. of, thence 3.4 mi NE. along Lambert Branch and Dummit Ridge Road; 300 ft W. of residence of Arthur Dummit; 25 ft N. of rd.; 9 ft S. of large chestnut tree; in N. edge of sandstone outcrop; standard tablet stamped "IT STA NO 60 M 1929"

X = 2.311.495

Y = 367.578

38 30 15.63

83 09 41.40

By T. W. Cayce, 1947; Book AH 56

Quincy, 0.2 mi from left bank of Ohio River; about 650 ft above C. & O. Ry. culvert over Briery Creek; about 500 ft below station; about 275 ft below rd. to landing; on property of C. & O. Ry.; 14 ft landside from centerline of landside track; 5 ft from fence; in concrete pedestal; on 2-in. iron pipe; USED standard cap designated "573"

X = 2.319.478

Y = 411.137

38 37 25.25

83 07 54.33

Friendship, 5.0 mi S. of post office, along U.S. Highway 52; 31 ft NE. of mailbox; 18 ft SE. of centerline of hwy.; 6 ft SW. of telephone pole; in concrete post; standard tablet stamped "TT 1 TWC 1947"

X = 2.315.698

Y = 416.339

38 38 17.12

83 08 41.16

Pond Run; 40 ft W. of junction of T-rd. NW.; on iron post; standard cap stamped "PRIM TRAV STA NO 8 1910 OHIO 522" (Top of pipe reported broken off, 1948)

X = 2.320.316

Y = 424,779

38 39 40.00

83 07 41.68

Friendship, 0.5 mi S. of post office, along U.S. Highway 52; 270 ft N. of concrete bridge over Rabbit Run; 120 ft N. of junction of cut—off rd. and hwy.; 30 ft NW. of centerline of hwy.; in concrete post; standard tablet stamped "TT 2 TWC 1947"

X = 2.326.602

Y = 436.002

38 41 30.16

83 06 20.67

Friendhsip, 1.8 mi N. of post office, along State Highway 125; 246 ft NW. of NW. corner of residence of T. R. Eisen; 33 ft SW. of 24-in. twin oak tree; 21 ft N. of centerline of hwy.; in NE. wingwall of concrete culvert; NGS standard disk stamped "D 79 1935"

X = 2,321,513

Y = 441,145

38 42 21.62

83 07 24.06

STATION

DESCRIPTION PLANE COORDINATES, FEET

LATITUDE 0 1 11 LONGITUDE 0 1

OBSOLETE MARKS (Cont'd.)

Friendship, 3.2 mi W. of post office, along State Highway 125; 126 ft ME. of ME. corner of residence of Mrs. J. Cuppett; 60 ft SE. of fence corner; 21 ft N. of centerline of hwy.; in NE. wingwall of concrete culvert; NGS standard disk stamped "E 79 1935"

Kv. N.) X = 2.315.121 Y = 446.065

38 43 11.02

83 08 43.95

Friendship, 4.0 mi W. of post office, along State Highway 125, thence 0.7 mi N. along OYO Scout Road; 26 ft SE. of centerline of rd.; 5 ft N. of 18-in. white oak tree; in concrete post; standard tablet stamped "TT 3 TWC 1947"

X = 2.313.278

Y = 450.971

38 43 59.71

83 09 06.46

Rexton, 1.8 mi S. of post office, along Montgomery Mountain Road; 19 ft W. of SW. corner of yard at residence of V. Lambert; 9 ft E. of centerline of rd.; in concrete post; standard tablet stamped "IT 8 TWC 1947 743" (Reported destroyed, 1961)

X = 2,322,436 Y = 384,709

38 33 03.67

83 07 21.14

Rexton, 3.7 mi S. of post office, along Montgomery Mountain Road; 21 ft SW. of twin sycamore tree; 11 ft E. of centerline of rd.; in concrete post; standard tablet stamped "TT 9 TWC 1947 912"

X = 2.322.982

Y = 376,002

38 31 37.54

83 07 15.60

By D. W. Pinkston, 1949; Book AH 134

Tannery, 4.0 mi S. of; 5.5 mi M. of State Highway 59 bridge over Kinniconick Creek, along Kinniconick Creek Road; 3.2 mi S. of Tannery School; 12 ft N. of SW. corner of armstrong church (built in 1953); 28 ft S. of NW. corner of church; 0.6 ft W. of W. wall of church; in concrete post; standard tablet stamped "TT STA NO 53 M 1929 652"

X = 2,288,178 Y = 374,759

38 31 29.24

83 14 33,72

Armstrong School, 1.5 mi N. of; 47 ft ME. of, and 6 ft lower than junction of new and old roadbeds; 1 ft NW. of boundary fence of Lewis County Wildlife Area; in concrete post; standard tablet stamped "86 EOM 1949 622"

X = 2.290.062

Y = 380.483

38 32 25.61

83 14 09-22

193 KY.-7 OHIO
GARRISON QUADRANGLE

38-083-12

STATION

DN DESCRIPTION PLANE COORDINATES, FEET

LATITUDE

LONGITUDE

THIRD-ORDER ELECTRONIC TRAVERSE

Final adjustment of 1977

LINE 1.

By W. C. Elder, 1959; Book AH 594

NGS triangulation station designated "POND RUN STATE FOREST LOOKOUT TOWER 1953"

Ky. N.) X = 2,304,027.85 Y = 419,937.77

38 38 54.054

83 11 07.712